



技术要求:
 1.膜壳最大压力为: 1000PSI(69KG/CM²),
 水介质温度: 1℃~49℃;
 不可用于腐蚀性液体场合;
 2.2芯及2芯以上均用三套鞍座箍带。
 注: 括号内尺寸参考尺寸。
 Technical requirements:
 Shell maximum pressure : 1000PSI,(69KG/CM²)
 Water medium temperature: 1 to 49;
 Can not be used in corrosive liquid occasions;
 Note: dimensions in brackets refer to dimensions.

长度编码 Length Code	L Inch (mm)	S Span (mm)	A Span (mm)	壳体重量 lb (kg)
25/14	19.09 (485)	16.72 (425)	3.94 (100)	7.0 (3.2)
25/21	26.06 (662)	23.72 (602)	3.94 (100)	9.5 (4.3)
25/40-1	45.08 (1145)	42.72 (1085)	7.87 (200)	16.5 (7.5)
25/40-2	85.08 (2161)	82.72 (2101)	7.87 (200)	31.2 (14.2)
25/40-3	125.08 (3177)	122.72 (3117)	7.87 (200)	45.8 (20.8)
25/40-4	165.08 (4193)	162.72 (4133)	7.87 (200)	60.5 (27.5)

8	内六角螺栓 Inner hexagonal head bolt	4	M5*1.5,304
7	月牙片 Crescent film	4	SA-213,304
6	膜密封圈 Film sealing ring	2	EPDM
5	产品序列号标签 Product serial number label	1	铜版纸 Art paper
4	大密封圈 Large sealing ring	2	EPDM
3	膜壳标签 Shell label	1	不干胶标签 Self-adhesive label
2	承压头 Pressure head	2	2205
1	壳体 Housing	1	环氧+玻纤 Epoxy + glass fiber
序号	名称	数量	材料

SIGNATURE		河北成达管业有限公司 HE BEI CHENGDA PIPES Co.,LTD		
NAME	DATE	比例 SCALE	材料 MATERIAL	型号 TYPE
DESIGN				W25E1000
REVIEW		数量 QUANTITY	光洁度 SMOOTH	描述 DESCRIPTION
				MEMBRANE HOUSING
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY		投影 PROJ	电脑编号 NO.	图号 DRAWING NO.
				CD-Z-15
DO NOT MEASURE THE DIMENSIONS.				单位 UNIT:MM