



技术要求:

- 1.膜壳最大压力为: 1000PSI(69KG/CM²),
- 水介质温度: 1℃~49℃;
- 不可用于腐蚀性液体场合;

注: 括号内尺寸参考尺寸.

Technical requirements:
 Shell maximum pressure : 1000PSI,(69KG/CM²)
 Water medium temperature: 1 to 49;
 Can not be used in corrosive liquid occasions;
 Note: dimensions in brackets refer to dimensions.

侧口	1"
名称	规格

长度编码 Length Code	L Inch (mm)	P Standard Inch (mm)	壳体重量 lb (kg)
1	56.49 (1435)	42 (1067)	27 (12)
2	96.49 (2451)	82 (2083)	37 (16.5)
3	136.49 (3467)	122 (3099)	48 (21.1)
4	176.49 (4483)	162 (4115)	58 (25.6)
5	216.49 (5499)	202 (5131)	68 (30.3)
6	256.49 (6515)	242 (6147)	78 (34.7)

13	月牙片Crescent film	4	SA-213, 304
12	内六角螺栓Inner hexagonal head bolt	4	M6*1,304
11	钢带护套Steel sheath	2or3	软质PVC Soft PVC
10	钢带螺母Steel strip nut	4or6	HPB59-1
9	承压头O型圈Pressure head O type ring	2	EPDM
8	大密封圈Large sealing ring	2	EPDM
7	产品序列号标签Product serial number label	1	铜版纸Art paper
6	侧口	2	2205
5	侧口螺母	2	316L
4	膜壳标签Shell label	1	不干胶标签Self-adhesive label
3	侧口密封圈	2	EPDM
2	承压头Pressure head	2	2205
1	壳体Housing	1	环氧+玻纤Epoxy + glass fiber
序号	名称	数量	材料

SIGNATURE			Winder 河北成达管业有限公司 HE BEI CHENGDA PIPES CO.,LTD		
DESIGN	NAME	DATE	比例 SCALE	材料 MATERIAL	型号 TYPE
REVIEW			数量 QUANTITY	光洁度 SMOOTH	描述 DESCRIPTION MEMBRANE HOUSING
THIS DRAWING CAN NOT BE USED WITHOUT PRIOR WRITTEN APPROVAL OF OUR COMPANY			投影 PROJ	电脑编号 NO.	图号 DRAWING NO. CD-Z-20
			DO NOT MEASURE THE DIMENSIONS.		